



## SAFETYBOX® A600/50 cod. CH006/5

**ASPIRATED SAFETY CABINET FOR THE STORAGE OF 15 LITRES OF CHEMICAL, ACID AND BASE PRODUCTS CERTIFIED ACCORDING TO 61010-1, EN 16121, EN 16122 NORMS, PPP52125 A**



- External dimensions: mm 600 x 500 x 720 (620) h
- Internal dimensions: mm 530 x 465 x 555 h
- Weight: Kg 45
- Internal volume: approx. 140 litres

- Completely produced in pickled and electrogalvanized steel, 10/10 mm thickness, painted with epoxy acid-proof powders and passage through thermic tunnel at 200° C. Thickness of painting from a minimum of 60µm (micron) to a maximum of 250µm (micron) as per UNI EN ISO 9001 procedure.
- **Certified palletized base:** new design of the base for easier transportation of the cabinet. **With removable cover.** Possibility to remove the base if necessary.
- **External monolithic construction** completely sealed. New building method with double cases, internal and external.
- Watertight bottom basin in electrogalvanized steel painted with epoxy anti-acid powders with drilled shelf. Capacity approx. 7 litres.
- Door opening up to 180° to allow an easy extraction of the shelf without tilting it.
- Key lock with **extractable cylinder (on demand “passe-partout kit” master key in case of lost keys).**
- Acid-proof hidden hinges.
- **Prepared for activated charcoal filter Carbox® (mod. F007).**
- **Termically protected electro aspirator IMQ IPX4** made of class V0 polymer to grant the highest level of self-extinguishing, in compliance with EN 60335-1, EN 60335-2-80 and EN 50366 norms.
- Input voltage: Volt 220/230.
- Max absorbed power: 21W.
- Fuse 5x20 F 500 µA.
- ON/OFF lamp.
- “Danger” warning stickers on the door (as per European Norms DIN 4844 and ISO 3864).
- Grounding connection to discharge build-up of static electricity.
- Levelling feet for balance.
- **Lifetime warranty “RC PRODOTTI”:** it covers any injury to persons and objects.
- Usage and maintenance manual.