

KEMFIRE® 1100 A type A cod.KF011A



ASPIRATED AND FILTERED SAFETY CABINET FOR THE COMBINED STORAGE OF CHEMICALS, ACIDS AND BASES, AND SOLID AND LIQUID FLAMMABLES CERTIFIED ACCORDING TO EN 14470-1, EN 61010-1, EN 16121, EN 16122 NORMS



- External dimensions: (WxDxH): mm 1100 x 510 x 1670
 - Internal dimensions: compartment for chemicals, acids and bases (WxDxH): mm 490+490 x 465 x 1020
 - Internal dimensions: compartment for flammables (WxDxH): mm 935 x 395 x 445
 - Weight: kg 300
 - Internal volume: 465+164 Liters
- Completely produced in **pickled and electrogalvanized steel** 10/10 mm painted with epoxy acid-proof powders electrostatically applied through thermic tunnel at 200°C. Smooth painting in the most delicate parts, and textured in the exposed parts. **Thickness of painting** from a minimum of **60 µm** (micron) to a maximum of **250 µm** (micron) as per UNI EN ISO 9001 procedure.
 - **External monolithic construction completely sealed.** New building method with double cases, internal and external.
 - “Danger” stickers for corrosive, harmful and toxic products on the chemicals compartment and “No Smoking” and “Fire” warning stickers on the flammables compartment, as required by European Norms DIN 4844 and ISO 3864.
 - **Key lock with extractable cylinder (on demand “passe-partout kit” master key in case of lost keys)**
 - Grounding connection to discharge build-up of static electricity.
 - Levelling feet for balance.
 - **Lifetime warranty “RC PRODOTTI”:** it covers any injury to persons and objects.
 - Usage and maintenance manual.
 - **Packaging with “Tipping over system®” device.**

UPPER COMPARTMENT FOR CHEMICAL, ACID AND BASE PRODUCTS

- **4 shelves adjustable in height** (2 for each compartment) made of electrogalvanized steel painted with epoxy acid-proof powders. Tray-shaped shelves to collect any liquid spillage of breakages. **Removable and adjustable shelves with anti-falling security lock by rack.** Collection capacity of the shelf approx. 7 litres. Loading capacity kg. 40/100.
- **Watertight bottom basins in electrogalvanized steel painted with epoxy anti-acid powders. Capacity approx. 13 litres.**
- Doors opening up to 180° to allow an easy extraction of the shelves without tilting them.
- Acid-proof hidden hinges.
- **Activated charcoal filter Carbox®** positioned inside the cabinet, easy to be replaced.
- **New electronic device Cunctator®** for charcoal filter replacement.
- **Termically protected electro aspirator IMQ IPX4** made of class V0 polymer to grant the highest level of self-extinguishing, in compliance with EN 60335-1, EN 60335-2-80 and EN 50366 norms.
- Input voltage: Volt 220/230.
- Max absorbed power: 65W.
- Fuse 5x20 F 500 µA.
- ON/OFF lamp.

LOWER COMPARTMENT FOR FLAMMABLE PRODUCTS

- Fire test carried out in accredited laboratories according to EN 1363-1 and UNI EN 1363-1.
- New fireproof insulation made of highly fire resistant material, completely ecological.

- **Internal body panels made of anti-scratch material, resistant to corrosive products.**
- **Inflatable trimming 8 + 6 cm (DIN 4102)**, that swells in case of fire, isolating the inside of the cabinet from the outside.
- **Extra inflatable trimming** with protection against “Cold and Hot fumes” and dusts.
- Self-closing doors with automatic return.
- **Safety closing system: in case of fire, automatically closes the door at a temperature of >50°C. Not electric.**
- Watertight bottom basin in electrogalvanized steel painted with epoxy anti-acid powders, with drilled shelf. Collection capacity approx. 9 litres. Loading capacity kg. 80.
- Natural internal ventilation system for vapours, equipped with two certified security valves for air recycling with automatic closure at $70 \pm 10^\circ \text{C}$. The valves are positioned at the top and at the bottom of the rear wall of the cabinet in order to grant the release of substances, as per normative. External connection collar \varnothing 100 mm.
- **Safety catch “Ignis-lock®”** that keeps the doors closed in case of fire.
- Anti-spark hinges.